

SPARC ENTERPRISE M4000 SERVER

MAINFRAME-CLASS RAS AND UNMATCHED INVESTMENT PROTECTION

KEY FEATURES

- Optimized for 24x7 mission critical computing and large shared memory applications
- Mainframe class reliability, availability, serviceability (RAS)
- Unmatched investment protection with no forklift upgrades - upgrade individual components, not the whole system
- Mix and match up to four SPARC64 VI and/or SPARC64 VII/VII+ processors in the same system
- 100% binary compatibility with earlier versions of your applications
- Built-in, no-cost, and flexible virtualization technology
- Ideal consolidation platform with up to two Dynamic Domains and support for thousands of Oracle Solaris Containers
- Accelerates database applications by 2x, cuts transaction times in half with Oracle's Storage F5100 Flash Array

Companies can't afford to have business-critical services go offline. To meet these increasing demands for compute services, platforms must be flexible and provide a cost-effective growth path. Oracle's midrange SPARC Enterprise M4000 server boasts reliability, flexibility, and binary compatibility in a value-priced server by combining the power of the Oracle Solaris operating system with mainframe RAS features. Built on the latest and most advanced SPARC64 VII/VII+ quad-core or SPARC64 VI dual-core processors, the SPARC Enterprise M4000 server delivers enterprise-class service levels for essential business applications, databases, and smaller consolidation projects.



The SPARC Enterprise M4000 server delivers main-frame class reliability, availability, and serviceability.

Investment Protection, Scalability, Reliability, and Flexibility

With the SPARC Enterprise M4000 servers, you can protect your IT investment with no forklift upgrades and scale out as needed. The option to mix and match different speeds/generations of SPARC64 processors in existing and new M-series servers uniquely protects investments and enables easy and low-cost upgrades not offered by IBM or HP.

In addition, mainframe-class RAS features come standard in the SPARC Enterprise M4000

server, including automatic recovery with instruction retry, up to 256 GB of system memory error-correcting code (ECC) protection with extended ECC support, guaranteed data path integrity, total SRAM and register protection, and configurable memory mirroring. In addition, the disks, power supply, and fans are redundant and hot-swappable, while the I/O cards are also hot-swappable. Many features unique to Oracle Solaris 10 enhance system reliability even further, including Predictive Self-Healing, which automatically identifies and isolates faults and provides specific guidance when action is required.

For more flexibility, the SPARC Enterprise M4000 server supports up to two Dynamic Domains with a high level of granularity: CPU board-level domains for large, mission-critical workloads requiring maximum isolation, and single-socket-level domains for finer granularity with high isolation. For maximum flexibility, each system can support thousands of Oracle Solaris Containers, which can create many private execution environments within a single Oracle Solaris instance.

Oracle Solaris: The World's Most Advanced Operating System

Only Oracle legally assures investment protection with Oracle Solaris with 100% binary compatibility for the past 15 years and counting. The SPARC Enterprise M4000 server is preinstalled with Oracle Solaris 10. Oracle Solaris 10 also delivers revolutionary features, including Dynamic Tracing (DTrace), Oracle Solaris ZFS, cryptographic infrastructures, IP filter, and User and Process Rights Management.

SPARC Enterprise M4000 Server Specifications

Processor	
Up to four SPARC64 VII/VII+ quad-core processors or dual-core SPARC64 VI processors	
Currently offered	<ul style="list-style-type: none"> • SPARC64 VII+ • SPARC64 VI
Also supported	<ul style="list-style-type: none"> • SPARC64 VII
SPARC V9 Architecture, ECC protected	
Cache per SPARC64 Level 1	<ul style="list-style-type: none"> • SPARC64 VII+: 64 KB D-cache and 64 KB I-Cache • SPARC64 VII: 64 KB D-cache and 64 KB I-Cache • SPARC64 VI: 128 KB D-cache and 128 KB I-Cache
Cache per SPARC64 Level 2	<ul style="list-style-type: none"> • SPARC64 VII+ 2.66GHz: 11 MB on-chip • SPARC64 VII 2.53GHz: 5.5 MB on-chip • SPARC64 VI 2.15GHz: 5 MB on-chip
Clock speed	<ul style="list-style-type: none"> • SPARC64 VII+: 2.66 GHz • SPARC64 VII: 2.53 GHz • SPARC64 VI: 2.15 GHz
System	
CPU	One or two CPU boards (CMU), two CPUs per board
Main memory	Up to 256 GB per using 8 GB DIMMs (64 GB per memory board x four boards)
I/O	<ul style="list-style-type: none"> • Up to five I/O slots with four PCIe slots and one PCI-X on one I/O tray • Up to 25 PCIe or PCI-X slots with optional External I/O Expansion Unit
System bus	High-speed, low-latency interconnect system bus with redundant data, address, and response crossbar interconnect

System bus bandwidth (memory)	32 GB/sec peak, 12.7 GB/sec stream (copy)
System bus bandwidth (I/O)	8 GB/sec peak
Service processor for system management	
Up to two Dynamic Domains	
Storage	
Boot device	Up to two internal, 2.5 in. SAS boot disks
External	Direct, SAN or NAS attached to StorageTek compatible tape libraries, flash array, and disk arrays, including StorageTek 3X00, 5X00, 6X00, 9X00, and Jx000 families and Storage F5100 Flash Array
Resource Management	
Dynamic Domains	
Oracle Solaris 10 Resource Manager including Oracle Solaris Containers	
Software	
Operating system	<ul style="list-style-type: none"> SPARC64 VII+ (2.66GHz): Oracle Solaris 10 (10/09) and XCP 1100 or later SPARC64 VII (2.53GHz): Oracle Solaris 10 (08/07) or later (requires installation of S10 Patch Bundle MU8) and XCP 1090 or later SPARC64 VI (2.15GHz): Oracle Solaris 10 (11/06) or later (plus patches) and XCP 1040 or later
Software included	<ul style="list-style-type: none"> Oracle Solaris 10 09/10 Preloaded XCP firmware
System monitoring (recommended, not included)	<ul style="list-style-type: none"> Oracle Enterprise Manager Ops Center
Environmental	
AC power	100–240 V AC 1-phase (50/60 Hz), 12 A per power cord, one or two power cords
Plug	NEMA-L6-20P (U.S.) or IEC 309-IP44 (INTL) IEC 60320 C19 connector
Receptacle type	IEC 60320 C20
Operating temperature	5°C to 35°C (41°F to 95°F), 20% to 80% relative humidity, noncondensing
Nonoperating temperature	-20°C to 60°C (-4°F to 140°F) 8% to 93% relative humidity, noncondensing
Altitude	Up to 3000 m (9,842 ft.)
Regulations	
Safety	CSA/UL-60950, EN60950, IEC950 CB Scheme with all national deviations
RFI/EMC	<ul style="list-style-type: none"> EN55022/CISPR22 Class A FCC CFR 47 Part 15 Class A EN61000-3-2 EN61000-3-3
Immunity	<ul style="list-style-type: none"> EN55024 EN61000-4-2, -4-3, -4-5, -4-6, -4-8, and -4/11
Regulatory markings	CE, FCC, ICES, C-Tick, VCCI, GOST-R, BSMI, MIC,

	CSA/UL
Other marks	WEEE and Chinese RoHS
Key RAS Features	
<ul style="list-style-type: none"> • End-to-end ECC protection • Guaranteed data path integrity • Automatic recovery with instruction retry • Total SRAM and register protection • Dynamic L1 and L2 cache line degradation • ECC and Extended ECC protection for memory, memory mirroring, and Predictive Self-Healing • Fault-isolated Dynamic Domains • Dynamic Reconfiguration • Auto Diagnosis and Recovery • Online Upgrades • Concurrent maintenance of disks, fans, and power supplies • Redundant network connections • Live operating system upgrades • Journaling file system • Hardened I/O drivers • Dynamic individual core or CPU offlining • Memory page retirement • Cluster support 	
Dimensions and Weight	
Height	26.3 cm (10.34 in.)
Width	44.4 cm (17.48 in.)
Depth	81.0 cm (31.9 in.)
Weight	84 kg (185 lb.)

Services

Visit www.oracle.com/acs for information on Oracle Advanced Customer Services offerings for Oracle server products.

Warranty

Visit oracle.com/sun/warranty for Oracle's global warranty support information on our products.

Contact Us

For more information about the SPARC Enterprise M4000 server, please visit oracle.com/sun or call +1.800.786.0404 to speak to an Oracle representative.



Copyright © 2011, Oracle and/or its affiliates. All rights reserved.

This document is provided for information purposes only and the contents hereof are subject to change without notice. This document is not warranted to be error-free, nor subject to any other warranties or conditions, whether expressed orally or implied in law, including implied warranties and conditions of merchantability or fitness for a particular purpose. We specifically disclaim any liability with respect to this document and no contractual obligations are formed either directly or indirectly by this document. This document may not be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose, without our prior written permission.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. UNIX is a registered trademark licensed through X/Open Company, Ltd. 1010

Hardware and Software, Engineered to Work Together